



(12) **United States Patent**
Penna et al.

(10) **Patent No.:** **US 9,636,112 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **CHIP ASSEMBLY FOR REUSABLE
SURGICAL INSTRUMENTS**

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

(72) Inventors: **Christopher Penna**, Guilford, CT (US);
Jonathan W. Sapienza, Orange, CT
(US); **Anne Nelson**, Guilford, CT (US);
Paul D. Richard, Shelton, CT (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 780 days.

(21) Appl. No.: **13/968,563**

(22) Filed: **Aug. 16, 2013**

(65) **Prior Publication Data**

US 2015/0048139 A1 Feb. 19, 2015

(51) **Int. Cl.**

A61B 17/04 (2006.01)
A61B 17/10 (2006.01)
A61B 17/068 (2006.01)
H05K 5/06 (2006.01)
H05K 7/14 (2006.01)
H01R 12/57 (2011.01)
H01R 12/72 (2011.01)
A61B 17/115 (2006.01)
A61B 17/00 (2006.01)
H01R 13/52 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/068** (2013.01); **A61B 17/1155**
(2013.01); **H01R 12/57** (2013.01); **H01R**
12/721 (2013.01); **H05K 5/069** (2013.01);
H05K 7/1427 (2013.01); **A61B 2017/0023**
(2013.01); **A61B 2017/0046** (2013.01); **A61B**
2017/00477 (2013.01); **H01R 13/5224**
(2013.01)

(58) **Field of Classification Search**

CPC **A61B 17/068**; **A61B 2017/00017**; **A61B**
2017/00398; **A61B 2017/2927**; **A61B**
6/58; **H05K 7/1427**; **H05K 5/069**
USPC **227/175.1-182.1**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,731,058 A 3/1988 Doan
4,898,360 A 2/1990 Vonhayn et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2 316 345 A1 5/2011
WO WO2013/051076 A1 4/2013

OTHER PUBLICATIONS

European Search Report EP 14 18 1116 dated Feb. 17, 2015.
(Continued)

Primary Examiner — Robert Long

(57) **ABSTRACT**

A chip assembly for use in a surgical stapler is provided. The chip assembly includes a housing assembly and a plug assembly. The housing assembly includes a base member, seal member, and a circuit board assembly. The base member defines a cavity for receipt of the circuit board assembly and the seal member is configured to be received about an open end of the base member. The plug assembly is configured to selectively engage the open end of the base member. The plug assembly includes a plug member and first and second contact members extending from the plug member. The first and second contact members are configured to be received within the cavity defined by the base member and engage the circuit board assembly when the plug assembly engages the housing assembly.

14 Claims, 12 Drawing Sheets

